

Delock Audio Adapter 8 pin Lightning™ male DAC 32 Bit/384 kHz Hi-Res to 2.5 mm 4 pin stereo jack female 10.5 cm

Description

This audio adapter by Delock enables the connection of a device or headset with a 2.5 mm 4 pin stereo jack male connector to an iPhone 7 or other mobile devices with 8 pin LightningTM port.

5N PCOCC Silver Plated Cable

The 5N PCOCC Silver Plated Cable supports higher transmission efficiency than copper and therefore offers the advantages of a very fast, crystal clear signal transmission as well as a lower electrical resistance. At the same time, the cable is very flexible and durable. Silver plated cables are especially used for high-end audio and video applications.



Item no. 66318

EAN: 4043619663187 Country of origin: China Package: Zip poly bag

Specification

- · Connectors:
 - 1 x 8 pin Apple LightningTM male >
 - 1 x 2.5 mm 4 pin stereo jack female
- Chipset: C100
- Cable gauge: 26 AWG
- · Lossless digital-analog audio decoding chipset
- 32 Bit / 384 kHz Hi-Res output capability
- 0 % Frequency Range Loss
- 98 dB noise reduction
- Length incl. connectors: ca. 10.5 cm

System requirements

- Device with a free Lightning[™] port
- Device or headset with a 2.5 mm 4 pin stereo jack male



Package content

• Audio adapter





Interface

connector:	1 x Lightning™ male
Connector 1:	1 x 2.5 mm 4 pin stereo jack female

Technical characteristics

Chipset:	C100
----------	------

Physical characteristics

Cable length incl. connector:	10,5
Conductor gauge:	26 AWG