

# Delock MDR male 36 pin solder connection with housing

## Description

This shielded MDR (Mini D Ribbon) male with soldering connection by Delock can be used for cable mounting and I/O applications.

### Protection by enclosure

The plastic housing protects the male connector from dirt and damage.

### Strain relief

The screw-on strain relief fixes the cable in the enclosure.



**Item no. 66624**

EAN: 4043619666249

Country of origin: China

Package: Poly bag

## Specification

- Connectors: 1 x MDR 36 male (2 rows) with soldering connection
- Pitch: 1.27 mm
- Useable for a cable gauge from 30 to 24 AWG
- Contact coating: gold plated, nickel plated
- Operating temperature: -25 °C ~ 85 °C
- Fire-resistance rating: 94V-0
- Housing material: plastic
- Dimensions (LxWxH): ca. 43.5 x 39.0 x 12.7 mm

## Package content

- MDR male
- Housing 2-part
- Strain relief 2-part
- 4 x screw
- 2 x locking screws
- 2 x nut



## Interface

connector:	MDR 36 male (2 rows) with soldering connection
------------	--

## Technical characteristics

Operating temperature:	-25 °C ~ 85 °C
------------------------	----------------

## Physical characteristics

Pitch distance:	1.27 mm
Housing material:	Plastic
Conductor gauge:	30 - 24 AWG
Length:	43,5 mm
Width:	39.0 mm
Height:	12.7 mm