

# Delock USB 20 Gbps Cable USB Type-C<sup>™</sup> male to male PD 3.0 100 W E-Marker 0.5 m black metal

# Description

This USB4<sup>™</sup> cable by Delock enables the connection of various devices, such as smart phones, monitors, external enclosures and docking stations, via a USB Type-C<sup>™</sup> or Thunderbolt<sup>™</sup> 3 port of a PC or laptop. The cable supports the transfer of USB as well as DisplayPort and PCI Express data.

#### USB4<sup>™</sup> 20 Gbps

The cable enables data transfer rates up to 20 Gbps when connecting USB4<sup>TM</sup>-compatible devices. Of course, USB 3.2 or USB 2.0 devices can also be connected.

# USB Power Delivery (USB PD 3.0) support up to 100 watt

Supports the USB Power Delivery 3.0 standard, which allows connected devices to be powered with up to 100 W (20 V / 5 A).

#### Metal housing and strain relief

Thanks to the elegant metal housing and sturdy strain relief on both sides, the cable is optimally protected against damage in everyday use.

Specification

Connectors:

2 x USB 20 Gbps USB Type-C™ male

- Downwards compatible to USB 3.2, USB 2.0 and Thunderbolt™ 3
- Chipset: E-Marker
- Connector with metal housing
- Cable with textile shielding
- Cable gauge:
  32 AWG data line
  22 AWG power line
- Cable diameter: ca. 5 mm
- · Contacts gold-plated



0,5 m

#### Item no. 80023

EAN: 4043619800230 Country of origin: China Package: Zip poly bag





- · Cable triple shielded
- Data transfer rate up to 20 Gbps
- Display resolution up to 3840 x 2160 @ 60 Hz
- (depending on the system and the connected hardware)
- Supports HDR10
- Supports HDCP 1.4 and 2.3
- Supports PCI Express 3.0 protocol (4 lanes)
- Supports DisplayPort 1.4a protocol
- Supports DisplayPort Alt Mode 2.0
- Dual channel, bi-directional data transfer
- USB Power Delivery (USB PD 3.0) support up to 100 watt (20 V / 5 A)
- Colour: black
- Length incl. connectors: ca. 0.5 m

# Package content

• USB cable

## Images





# General

| Cable finishing: | textile coating  |
|------------------|--|
| Specification:   | HDCP 1.4<br>USB 10 Gbps<br>DisplayPort 1.4<br>HDR10<br>PCI Express 3.0<br>HDCP 2.3<br>USB Power Delivery 3.0 |

## Interface

| Connector 1: | 1 x USB Type-C™ male |
|--------------|----------------------|
| Connector 2: | 1 x USB Type-C™ male |

# **Technical characteristics**

| Data transfer rate:        | 10 Gbps             |
|----------------------------|---------------------|
| Maximum screen resolution: | 3840 x 2160 @ 60 Hz |

# **Physical characteristics**

| Housing material: | Aluminium                             |
|-------------------|---------------------------------------|
| Pin finishing:    | gold-plated                           |
| Conductor gauge:  | 32 AWG data line<br>22 AWG power line |
| Shielding:        | triple                                |
| Length:           | 50 cm                                 |
| Colour:           | black                                 |
| Cable diameter:   | 5 mm                                  |