

# Delock USB 2.0 Cable USB Type-C™ male to male PD 3.1 240 W E-Marker 2 m red metal

## Description

This USB cable by Delock enables the connection between a device with a USB Type-C™ connector and a PC or a laptop equipped with a free USB Type-C™ port.

## USB Power Delivery (USB PD 3.1) support up to 240 watt

Support for the Extended Power Range resp. USB Power Delivery 3.1 standard means that connected devices can be supplied with power, up to 240 W (48 V / 5 A) is possible.

## Metal housing and strain relief

Thanks to the elegant metal housing and sturdy strain relief on both sides, the cable is optimally protected against damage in everyday use.



2 m

**Item no. 80051**

EAN: 4043619800513

Country of origin: China

Package: Zip poly bag

## Technical details

- Connectors:  
2 x USB Type-C™ 2.0 male
- Chipset: E-Marker
- Connector with metal housing
- Cable gauge:  
26 + 28 AWG data line  
22 AWG power line
- Cable diameter: ca. 5 mm
- Contacts gold-plated
- Connectors gold-plated
- Cable triple shielded
- Data transfer rate up to 480 Mbps
- USB Power Delivery (USB PD 3.1) support up to 240 watt (48 V / 5 A)
- Colour: black / red
- Length incl. connectors: ca. 2 m

---

## Package content

- USB cable

---

## Images



## General

|                |         |
|----------------|---------|
| Specification: | USB 2.0 |
|----------------|---------|

## Interface

|              |                      |
|--------------|----------------------|
| Connector 1: | 1 x USB Type-C™ male |
| Connector 2: | 1 x USB Type-C™ male |

## Technical characteristics

|                     |          |
|---------------------|----------|
| Chipset:            | E-Marker |
| Data transfer rate: | 480 Mbps |
| Maximum load:       | 240 W    |
| Maximum current:    | 5 A      |
| Voltage:            | 48 V     |

## Physical characteristics

|                      |                                                           |
|----------------------|-----------------------------------------------------------|
| Connector finishing: | gold-plated                                               |
| Pin finishing:       | gold-plated                                               |
| Conductor gauge:     | 26 AWG data line<br>28 AWG data line<br>22 AWG power line |
| Shielding:           | triple                                                    |
| Length:              | 2 m                                                       |
| Colour:              | black / red                                               |
| Cable diameter:      | 5 mm                                                      |