Delock Cable mini DisplayPort 1.2 male with screw > HDMI male 4K Active black 3 m

Description

This cable enables you to connect a HDMI monitor through a free mini DisplayPort interface. The cable supports a resolution up to Ultra HD (4K) and is backward compatible to Full-HD 1080p. The screw of the mini DisplayPort connector secures the connection and prevents accidental unplugging of the cable.



Item no. 83731

EAN: 4043619837311

Country of origin: China

Package: Zip poly bag

Specification

- Connector:
  mini DisplayPort 20 pin male with screw >
  HDMI-A 19 pin male
- Input = mini DisplayPort; Output = HDMI
- Screw type: #4-40, thread type UNC, thread class 3A, American Standard Screw
- Chipset: Parade PS171
- DisplayPort 1.2 and High Speed HDMI specification
- Cable gauge: 32 AWG
- Cable diameter: ca. 5.5 mm
- Gold-plated connector
- Active cable, for graphics cards with DP and DP++ output
- Transfer of audio- and video signals
- Supports a resolution up to 4K (4096 x 2160 pixel @ 24 Hz or 3840 x 2160 pixel @ 30 Hz) - depending on the system and the connected hardware
- Supports 3D displays (1080p @ 120 Hz)
- Supports HDCP 1.3
- Supports Eyefinity
- Audio input formats: 8-channel LPCM, compressed audio (AC-3, DTS) and HBR audio format up to 24 Bit audio sample size and 192 kHz sample rate

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- 2 x ferrite core
- Cable length: ca. 3 m (incl. connector)
- Colour: black
- OS independent, no driver installation necessary

System requirements

- A free mini DisplayPort female port

Package content

- Cable mini DisplayPort to HDMI

Images



© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.