

# Delock Cable DisplayPort 1.2 male > High Speed HDMI-A male passive 4K 30 Hz 3 m white

#### **Description**

This cable by Delock enables the connection between devices, e.g. a monitor, with HDMI connector to a DisplayPort interface.



#### Item no. 83819

EAN: 4043619838196 Country of origin: China Package: Retail Box

#### **Specification**

- Connectors:
  - 1 x DisplayPort 20 pin male >
  - 1 x High Speed HDMI-A 19 pin male
- Chipset: Parade PS8402A
- DisplayPort 1.2a and High Speed HDMI specification
- Passive cable (level shifter), suitable only for graphics cards with DP++ output
- Signal direction: DisplayPort input > HDMI output
- Cable gauge: 30 AWG
- Cable diameter: ca. 6 mm
- Twisted-pair cabling
- Copper conductor
- Gold-plated connectors
- Triple shielded cable
- · Transfer of audio and video signals
- Data transfer rate up to 10.2 Gb/s
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- · Colour: white
- Length incl. connectors: ca. 3 m



## System requirements

• One free DisplayPort DP++ female

## **Package content**

• DisplayPort to HDMI cable

## **Images**





#### General

| Specification: | DisplayPort 1.2a |
|----------------|------------------|
|                | High Speed HDMI  |

#### Interface

| Connector 1: | 1 x DisplayPort male |
|--------------|----------------------|
| Connector 2: | 1 x HDMI-A male      |

## **Technical characteristics**

| Chipset:                   | Parade PS8402A      |
|----------------------------|---------------------|
| Data transfer rate:        | 10.2 Gb/s           |
| Maximum screen resolution: | 3840 x 2160 @ 30 Hz |

## **Physical characteristics**

| Connector finishing: | gold-plated |
|----------------------|-------------|
| Pin finishing:       | gold-plated |
| Conductor material:  | copper      |
| Conductor gauge:     | 30 AWG      |
| Shielding:           | triple      |
| Length:              | 3 m         |
| Colour:              | white       |