Delock Cable SATA 6 Gb/s 22 pin receptacle straight > SATA 7 pin receptacle + Floppy 4 pin power receptacle (5 V) 30 cm

Description

This cable by Delock enables the connection of a device with 22 pin SATA interface over a free SATA port and a free 4 pin Floppy power interface of the motherboard.



ca. 30 cm

Item no. 84849

EAN: 4043619848492

Country of origin: China

Package: Zip poly bag

Specification

- Connector:
  SATA 6 Gb/s 22 pin (7 pin data + 15 pin power) receptacle straight >
  SATA 6 Gb/s 7 pin receptacle upwards angled + Floppy 4 pin power receptacle
- Compatible to motherboards of the Fujitsu D3003/3313 series and Gigabyte GA-H110TN
  Mini-ITX series
- Data transfer rate up to 6 Gb/s
- Downwards compatible to SATA 1.5 Gb/s and 3 Gb/s
- Version with 3 power wires (black = GND, red = 5 V)
- Voltage: 5 V
- Cable gauge:
  30 AWG data line
  22 AWG power line
- Length without connector: ca. 30 cm

System requirements


© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- A free SATA interface
- A free Floppy power plug

Package content

- SATA cable

Images



© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Specification:	SATA 6 Gb/s

Interface

Connector 1:	1 x SATA 6 Gb/s 22 pin receptacle
Connector 2:	1 x Floppy 4 pin power receptacle 1 x SATA 6 Gb/s 7 pin receptacle

Technical characteristics

Data transfer rate:	6 Gb/s
Voltage:	5 V

Physical characteristics

Conductor gauge:	30 AWG data line 22 AWG power line
Length:	30 cm

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.