

Delock DisplayPort cable 8K 60 Hz 2 m DP 8K certified

Description

This certified DisplayPort cable by Delock is used to connect devices with a DisplayPort interface, such as monitors, beamers or televisions, to a PC or laptop. Supporting a maximum bandwidth of 32.4 Gb/s, content can be displayed in 8K Ultra HD (7680 x 4320 @ 60 Hz) resp. 5K (5120 x 2880 @ 120 Hz) and 4K Ultra HD (3840 x 2160 @ 240 Hz) resolution. The high-quality, triple-shielded cable also significantly improves the quality of audio transmissions with a sampling rate of up to 1536 kHz.



EAN: 4043619856602 Country of origin: China Package: Retail Box

Specification

- Connectors:
 - 1 x DisplayPort 20 pin male >
 - 1 x DisplayPort 20 pin male
- DisplayPort 1.4 specification
- Downwards compatible to DisplayPort 1.3, 1.2 and 1.1
- DisplayPort® DP 8K certified cable
- Pin 20 not connected
- Cable gauge: 34 AWG
- Cable diameter: ca. 4.5 mm
- Copper conductor
- Triple shielded cable
- Contacts gold-plated
- Transmission of audio and video signals
- Data transfer rate up to 32.4 Gb/s
- Resolution up to:

Display with DSC support:

7680 x 4320 @ 60 Hz

5120 x 2880 @ 120 Hz

3840 x 2160 @ 240 Hz

Display without DSC support:





7680 x 4320 @ 30 Hz 5120 x 2880 @ 60 Hz 3840 x 2160 @ 120 Hz (depending on the system and the connected hardware)

- Supports Display Stream Compression 1.2 (DSC)
- Supports HDR
- Supports HDCP 1.4 and 2.2
- Supports HBR3 (8.1 Gb/s) data rate
- Up to 32 audio channels for speakers
- Up to 1536 kHz audio sampling rate
- Supports colour sampling in 4:4:4, 4:2:2 and 4:2:0 format
- Colour: black
- Length incl. connectors (L): ca. 2 m

System requirements

• A free DisplayPort interface

Package content

• DisplayPort cable

Images





General

| Specification: | HDCP 1.4 |
|----------------|-----------------|
| | HDCP 2.2 |
| | DisplayPort 1.4 |
| | HDR10 |

Interface

| Connector 1: | 1 x DisplayPort male |
|--------------|----------------------|
| Connector 2: | 1 x DisplayPort male |

Technical characteristics

| Data transfer rate: | 32.4 Gb/s |
|----------------------------|---------------------|
| Maximum screen resolution: | 7680 x 4320 @ 60 Hz |

Physical characteristics

| Pin finishing: | gold-plated |
|---------------------|-------------|
| Conductor material: | copper |
| Conductor gauge: | 34 AWG |
| Shielding: | triple |
| Length: | 2 m |
| Colour: | black |