

Delock PoweredUSB cable male 24 V to 2 x 4 pin male 3 m for POS printers and terminals

Description

This PoweredUSB cable by Delock can be used to connect a device with 2 x 4 pin port to a PC or hub with PoweredUSB 24 V port. It is suitable for connecting various POS devices such as printers and terminals, e.g. by IBM, NCR or Hypercom. The cable is used both for data transmission and for power supply of the connected device.



Item no. 85952

EAN: 4043619859528

Country of origin: China

Package: Zip poly bag

Specification

- Connectors:
 - 1 x PoweredUSB male 24 V >
 - 1 x Male 2 x 4 pin
- PoweredUSB specification
- Voltage: 24 V
- Cable gauge:
 - 26 AWG data line
 - 20 AWG power line
- Cable diameter: ca. 6.5 mm
- Cable double shielded
- Data transfer rate up to 480 Mbps
- Colour: black
- Length incl. connectors: ca. 3 m

System requirements

- PC or hub with a free PoweredUSB 24 V female port

- Device with a free 2 x 4 pin female port

Package content

- PoweredUSB cable

Images



General

| | |
|----------------|------------|
| Specification: | PoweredUSB |
|----------------|------------|

Interface

| | |
|--------------|--------------------------|
| Connector 1: | 1 x PoweredUSB male 24 V |
| Connector 2: | 2 x Mini DIN 4 pin |

Technical characteristics

| | |
|---------------------|------------------------|
| Data transfer rate: | USB 2.0 up to 480 Mb/s |
| Voltage: | 24 V |

Physical characteristics

| | |
|------------------|---------------------------------------|
| Conductor gauge: | 26 AWG data line 20 AWG power line |
| Shielding: | double |
| Length: | 3 m |
| Colour: | black |