

Delock HDMI to DisplayPort cable 4K 30 Hz 10 m

Description

This cable by Delock enables the connection between devices, e.g. a monitor, with DisplayPort connector to a HDMI interface.



Item no. 85968

EAN: 4043619859689 Country of origin: China Package: Zip poly bag

Specification

- Connectors:
 - 1 x HDMI-A male
 - 1 x USB Type-A male (power supply) >
 - 1 x DisplayPort male
- Signal direction: HDMI input > DisplayPort output
- Chipset: STDP2600
- DisplayPort 1.2 and High Speed HDMI specification
- Cable gauge: 28 AWG
- Cable diameter: ca. 7.2 mm
- Contacts gold-plated
- Transmission of audio and video signals
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Supports 3D displays (1080p @ 120 Hz)
- 2 x ferrite core
- · Colour: black
- Dimensions of signal amplifier (LxWxH): ca. 8.00 x 2.20 x 1.35 cm
- Length incl. connectors: ca. 10 m



System requirements

• A free HDMI female

Package content

• HDMI to DisplayPort cable

Images





General

| Specification: | DisplayPort 1.2 High Speed HDMI |
|----------------|--|
| Interface | |
| Connector 1: | 1 x HDMI-A male 1 x USB Type-A male |
| Connector 2: | 1 x DisplayPort male |

Technical characteristics

| Chipset: | STDP2600 |
|----------------------------|---------------------|
| Maximum screen resolution: | 3840 x 2160 @ 30 Hz |

Physical characteristics

| Ferrite core: | 2 x |
|---------------------|-------------|
| Pin finishing: | gold-plated |
| Conductor material: | copper |
| Conductor gauge: | 28 AWG |
| Shielding: | triple |
| Diameter: | 7.2 mm |
| Length: | 10 m |
| Colour: | black |