

Delock Modular Wall Outlet flush mount 2 Port Cat.6A LSA

Description

This network wall outlet by Delock can be installed in-wall or on a back box with 60 mm mounting holes. The LSA blocks can be used with a punch down tool; the horizontal cable feed allows a flexible installation.



Item no. 86195

EAN: 4043619861958 Country of origin: China Package: Zip poly bag

Specification

- Connectors: external: 2 x RJ45 jack internal: 2 x LSA block
- Cat.6A specification
- Shielded (STP)
- TIA-568A/B pinout
- Cable diameter up to 0.644 mm (22 24 AWG)
- Material: zinc die cast
- Integrated name plate
- Design suitable central plate 50 x 50 mm
- Mounting holes 60 mm
- Colour: pure white RAL 9010
- Dimensions (LxWxH): ca. 80 x 80 x 39 mm

Package content

Modular Wall Outlet

DATASHEET



• 2 screws

Images





DATASHEET



General

Suitable for conductor gauge:	22 - 24 AWG
Mounting type:	in-wall

Interface

External:	2 x RJ45 jack
Internal:	2 x LSA block

Technical characteristics

Category:

Physical characteristics

Housing colour:	white
Length:	80 mm
Width:	80 mm
Height:	38.2 mm