

# **Delock Gigabit PoE+ Splitter 802.3at**

## Description

This Power over Ethernet Splitter by Delock can supply power to a non-PoE-enabled device, such as an IP camera or a WLAN access point. The splitter is connected to the network cable and powered by a PoE injector (PSE). The DC jack provides an adjustable voltage of 5 V / 7.5 V / 9 V or 12 V with a maximum of 2 A for the connected equipment. Simultaneously, a 1 Gb/s Ethernet connection is available. The compact size and integrated wall mounting enable space-saving installation.



#### Item no. 87657

EAN: 4043619876570 Country of origin: Taiwan, Republic of China

Package: White Box

### **Specification**

- · Connector:
  - 1 x RJ45 jack (Data + Power In)
  - 1 x RJ45 jack (Data Out)
  - 1 x DC jack 5.5 x 2.1 mm (Power Out)
- Output Power: DC 5 V / 7.5 V / 9 V / 12 V (selectable), 2.0 A max.
- Data transfer rate up to 1 Gb/s
- LED indicator (power, selected voltage)
- Supports IEEE 802.3at (PoE+) and 802.3af (PoE)
- · Wall mounting integrated in the housing
- Power consumption: max. 2 W
- Operating temperature: 0 °C ~ 45 °C
- Dimensions (LxWxH): ca. 78 x 72 x 27 mm

#### Specification of power connector

- · Ground outside, plus inside
- Dimensions:

inside: ø ca. 2.1 mm



outside: ø ca. 5.5 mm length: ca. 9 mm

# **Package content**

- PoE Splitter
- DC cable 5.5 x 2.1 mm male > 5.5 x 2.1 mm male ca. 30 cm (black)
- DC cable 5.5 x 2.1 mm male > 5.5 x 2.5 mm male ca. 30 cm (red)
- User manual

#### **Images**





