

Delock USB Type-C™ Docking Station with M.2 Slot - 4K HDMI / USB / LAN / PD 3.0

Description

This docking station by Delock can be connected to a computer with a USB-C™ DP Alt Mode or Thunderbolt™ 3 port and provides a variety of interfaces. A monitor can be operated at the **HDMI output**. **Two built-in USB 3.2 Gen 1** ports allow the use of peripherals and a connector for **gigabit network** completes the features.

Slot for M.2 SSD with key B

On the bottom is an **M.2 slot**. An M.2 SATA SSD in 2280, 2260, 2242 or 2230 format can be connected to this slot.

USB Power Delivery (USB PD 3.0) support up to 100 watt

The docking station has a USB Type-C™ Power Delivery port to connect the power supply of the laptop or tablet to charge it. The docking station can also be used without a power supply.

Small sturdy helper

Due to its **small dimensions and its sturdy housing**, this Delock docking station is particularly suitable for travelling. It can simply be packed into the bag together with the laptop or tablet and used as needed.



Item no. 87767

EAN: 4043619877676

Country of origin: China

Package: Retail Box

Specification

- Connectors:
 - 1 x USB Type-C™ male
 - 2 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
 - 1 x HDMI-A female
 - 1 x Gigabit LAN 10/100/1000 Mbps RJ45 jack
 - 1 x USB Type-C™ female (power supply)
 - 1 x 67 pin M.2 key B slot
- Resolution up to 3840 x 2160 @ 30 Hz
(depending on the system and the connected hardware)
- Transmission of audio and video signals
- Supports HDCP 1.4 and 2.2

- Input power: 1 x USB Type-C™ female max. 100 W
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key B or key B+M based on SATA
- Metal housing
- LED indicator for power and access
- Cable length without connector: ca. 18 cm
- Colour: grey
- Dimensions (LxWxH): ca. 123 x 50 x 14 mm

System requirements

- Android 9.0 or above
- Chrome OS 78.0 or above
- iPad Pro (3rd Generation) or above
- Linux Kernel 4.6.4 or above
- Mac OS 10.15.3 or above
- Windows 8.1/8.1-64/10/10-64
- Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free Thunderbolt™ 3 port

Package content

- USB-C™ docking station
- User manual

Images



General

| | |
|-----------------------------|--|
| Supported operating system: | Android 9.0 or above Chrome OS 78.0 or above Linux Kernel 4.6.4 or above Mac OS 10.15.3 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (2018) |
| Supported module: | M.2 modules in format 2280, 2260, 2242 and 2230 with key B or key B+M based on SATA |

Interface

| | |
|--------------|---------------------------------------|
| Connector 1: | 1 x USB Type-C™ male |
| Connector 2: | 2 x USB 5 Gbps Type-A female |
| connector 3: | 1 x HDMI-A female |
| connector 4: | 1 x Gigabit LAN RJ45 jack |
| Input: | 1 x USB Type-C™ female (power supply) |
| Internal: | 1 x 67 pin M.2 key B slot |

Technical characteristics

| | |
|----------------------------|---------------------|
| Maximum screen resolution: | 3840 x 2160 @ 30 Hz |
|----------------------------|---------------------|

Physical characteristics

| | |
|---------|--------|
| Length: | 123 mm |
| Width: | 50 mm |
| Height: | 14 mm |
| Colour: | grey |