

Delock USB Type-C™ Docking Station 4K - Dual HDMI MST / USB 3.2 / SD / LAN / PD 3.0

Description

This docking station by Delock can be connected to a computer with a USB-C™ DP Alt Mode or Thunderbolt™ 3 port and provides a variety of interfaces. **Two monitors can be operated simultaneously** at the HDMI output ports. **Two built-in USB ports** allow the use of peripherals, and connections for **Gigabit network**, as well as an **SD and Micro SD** card reader, complete the features.



Multi-Stream Transport (MST)

The product is an MST hub and supports the extended desktop configuration of DisplayPort. This allows multiple monitors to be combined into one large display. Thereby the docking station supports a maximum resolution of up to **4K 60 Hz** per monitor.

USB Power Delivery (USB PD 3.0) support up to 85 watt

The docking station has a USB Type-C™ Power Delivery port to connect the power supply of the laptop or tablet to charge it. In addition it also supplies the USB ports with power. The docking station can also be used without a power supply.

Small sturdy helper

Due to its **small dimensions and its sturdy housing**, this Delock docking station is particularly suitable for travelling. It can simply be packed into the bag together with the laptop or tablet and used as needed.

Item no. 87774

EAN: 4043619877744

Country of origin: China

Package: Retail Box

Specification

- Connectors:
 - 1 x USB Type-C™ male
 - 1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
 - 1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female - Battery Charging specification BC1.2
 - 1 x SD / SDHC / SDXC slot
 - 1 x Micro SD / SDHC / SDXC slot

- 2 x HDMI-A female
 - 1 x Gigabit LAN 10/100/1000 Mbps RJ45 jack
 - 1 x USB Type-C™ PD female (power supply)
 - Maximum resolution (depending on the system and the connected hardware):
 - DisplayPort 1.4 Multi-Stream Transport (MST):
2 displays: up to 3840 x 2160 @ 60 Hz
 - DisplayPort 1.2 Multi-Stream Transport (MST):
2 displays: up to 3840 x 2160 @ 30 Hz
 - Transmission of audio and video signals
 - Functions: Mirrored or Extended (Windows only)
 - It can be used two memory cards at the same time
 - Data can be exchanged directly between two connected memory cards
 - Supports HDCP 1.4 and 2.2
 - Supports HDR
 - Output power for host: max. 85 W
 - Metal housing
 - Cable length without connectors: ca. 20 cm
 - Colour: grey
 - Dimensions (LxWxH): ca. 115 x 59 x 14 mm
-

System requirements

- Chrome OS 83.0 or above
 - iPad Pro (2018)
 - Linux Kernel 5.4 or above
 - Mac OS 10.15.6 or above
 - Surface Pro 7
 - Windows 8.1/8.1-64/10/10-64
 - Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free Thunderbolt™ 3 port
-

Package content

- USB-C™ docking station
- User manual

Images



Maximum resolution (depending on the system and the connected hardware)

DisplayPort 1.4 Input:	
Single Display	1-EDoP: 3840 x 2160 @ 60 Hz
Dual Display 50/7	1-EDoP + HDM: 2 x 3840 x 2160 @ 60 Hz
DisplayPort 1.2 Input:	
Single Display	1-EDoP: 3840 x 2160 @ 30 Hz
Dual Display 50/7	1-EDoP + HDM: 2 x 3840 x 2160 @ 30 Hz

General

Supported operating system:	Chrome OS 83.0 or above Linux Kernel 5.4 or above Mac OS 10.15.6 or above Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (2018)
-----------------------------	---

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz
----------------------------	---------------------

Physical characteristics

Cable length:	20 cm (without connector)
Length:	115 mm
Width:	59 mm
Height:	14 mm
Colour:	grey