

# Delock HDMI Video Capture Stick USB Type-C™

### Description

This **HDMI capture** stick by Delock can be used to transfer video signals, for example from a digital camera to a PC.

#### USB Video Class (UVC) standard

The connected computer or tablet / smartphone treats the input camera signal like a **webcam**, making the device excellent for **video conferencing or live streaming** when used together with a camcorder or action cam.

#### HDMI video and audio capture

The capture stick allows recording from HDMI sources with a maximum of 4K @ 30 Hz resolution; the recording is compressed up to 1080p at 30 Hz.



- The output of a stereo signal is mono summed.
- · Videos with HDCP copy protection cannot be recorded.

## **Specification**

- Connectors:
  - 1 x HDMI-A female
  - 1 x USB 2.0 Type-C<sup>™</sup> male
- Chipset: MS2109
- Maximum resolution (Input): 3840 x 2160 @ 30 Hz
- Maximum resolution (record): 1920 x 1080 @ 30 Hz
- Output support for YUY2, MJPG
- Frame rates:

1920 x 1080 MJPEG: 30 fps, YUY2: 5 fps 1360 x 768 MJPEG: 30 fps, YUY2: 8 fps 1280 x 720 MJPEG: 60 fps, YUY2: 10 fps 1600 x 1200 MJPEG: 30 fps, YUY2: 5 fps 1280 x 960 MJPEG: 50 fps, YUY2: 8 fps 800 x 600 MJPEG: 60 fps, YUY2: 20 fps 640 x 480 MJPEG: 60 fps, YUY2: 30 fps



#### Item no. 88309

EAN: 4043619883097 Country of origin: China Package: Retail Box

#### **DATASHEET**



- Audio recording format:
  16 bit stereo 48 kHz / 16 bit mono 96 kHz
- UVC standard for USB Video
- UAC standard for USB Audio
- Plug & Play
- USB Bus powered (no additional power supply required)
- Dimensions (LxWxH): ca. 66 x 24 x 10 mm

#### System requirements

- PC with UVC support
- PC or laptop with a free USB Type-C<sup>™</sup> port

## Package content

- HDMI video capture stick
- User manual

#### Images







### Interface

Output:	1 x USB Type-C™ male
Input:	1 x HDMI-A female

## **Physical characteristics**

Housing colour:	black
Housing material:	Plastic
Length:	66.0 mm
Width:	24 mm
Height:	10 mm