

# Delock WLAN 802.11 ac/a/b/g/n Antenna RP-SMA plug 4 - 5 dBi omnidirectional with tilt joint black

## Description

This Wireless LAN antenna can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals.

Bluetooth



RP-SMA

**Item no. 88393**

EAN: 4043619883936

Country of origin: Taiwan,  
Republic of China

Package: Zip poly bag

## Specification

- Connector: RP-SMA plug
- Frequency range:  
2.4000 - 2.4835 GHz  
5.1500 - 5.7250 GHz
- Antenna gain: 4 - 5 dBi
- Impedance: 50 Ohm
- Polarisation: linear, vertical
- VSWR: 2.0
- Operating temperature: -20 °C ~ 65 °C
- Housing material: TPEE
- Colour: black
- Length:  
ca. 195.00 mm (with tilt joint)  
ca. 165.00 mm (without tilt joint)
- Diameter:  
ca. 6.00 mm (top)  
ca. 12.50 mm (RP-SMA)





## System requirements

- Device with a free RP-SMA jack

## Package content

- WLAN antenna

## Images



## General

Suitable for indoor:	yes
----------------------	-----

## Interface

connector:	RP-SMA plug
------------	-------------

## Technical characteristics

Frequency range:	2.4000 GHz - 2.4835 GHz 5.1500 - 5.7250 GHz
Antenna gain:	4 - 5 dBi
Beam width horizontal:	360°
Impedance:	50 Ω
Operating temperature:	-20 °C ~ 65 °C
Polarisation:	linear vertical
VSWR:	2.0

## Physical characteristics

Housing colour:	black
Housing material:	TPEE
Diameter:	12.5 cm
Length:	19.6 cm