



Delock WLAN 802.11 ac/a/b/g/n Antenna SMA plug 2 dBi omnidirectional with tilt joint black

Description

This Wireless LAN antenna can be connected to a WLAN device with SMA interface, in order to send and receive signals.



Item no. 89437

EAN: 4043619894376 Country of origin: Taiwan, Republic of China

Package: Retail Box

Specification

· Connector: SMA plug

• Frequency range:

2.400 - 2.500 GHz

5.150 - 5.875 GHz

Antenna gain: 2 dBi

• Impedance: 50 Ohm

· Polarisation: linear, vertical

• VSWR: 2.0

• Operating temperature: -10 °C ~ 55 °C

· Housing material: ABS

• Colour: black

• Length:

ca. 111.70 mm (with tilt joint) ca. 83.40 mm (without tilt joint)

• Diameter:

ca. 7.80 mm (top)

ca. 10.00 mm (SMA)



System requirements


• Device with a free SMA jack


Package content


• WLAN antenna

Images













Interface

connector:	SMA Stecker	

Technical characteristics

Frequency range:	2.400 - 2.500 GHz 5.150 - 5.875 GHz
Gain:	2 dBi
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 55 °C
Polarisation:	linear vertical
VSWR:	2.0

Physical characteristics

Housing material:	ABS
Diameter connector:	10.00 mm
Length with tilt joint:	111.70 mm
Length without tilt joint:	83.40 mm
Colour:	black