

Delock PCI Express x4 Card > 1 x external USB Type-C[™] female + 1 x external USB 3.1 Gen 2 Type-A female

Description

This PCI Express card by Delock expands the PC by two external USB 3.1 ports. Different USB devices, such as docking stations, card readers, external enclosures etc., can be connected to the card.

Note

A data transfer rate of up to 10 Gbps per port is possible, due to the Asmedia chipset ASM2142. If two USB 3.1 devices are connected, they each support 10 Gbps.



Item no. 89898

EAN: 4043619898985 Country of origin: Taiwan, Republic of China

Package: Retail Box

Specification

• Connectors:

external:

1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female

1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female internal:

1 x SATA 15 pin power connector

1 x PCI Express x4, V3.0

- Chipset: Asmedia ASM2142
- Data transfer rate up to:

SuperSpeed USB 10 Gbps,

SuperSpeed USB 5 Gbps,

Hi-Speed 480 Mbps,

Full-Speed 12 Mbps,

Low-Speed 1.5 Mbps

- Power supply via PCI Express interface or via SATA 15 pin power connector
- Electrical power:

USB Type-CTM: max. 15 watt (5 V / 3 A)

USB Type-A: max. 4.5 watt (5 V / 0.9 A)



- Supports eXtensible Host Controller Interface (xHCI) specification 1.1
- Supports UASP

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, ex Linux Kernel 4.15.3
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

Package content


- PCI Express card SuperSpeed USB 10 Gbps
- Low profile bracket
- Driver CD
- User manual

Images













General

Linux Kernel 4.15 or above
LITIUX NOTICE 4.13 OF ABOVE
Windows 10 32-Bit
Windows 10 64-Bit
Windows 7 32-Bit
Windows 7 64-Bit
Windows 8.1 32-Bit
Windows 8.1 64-Bit

Interface

External:	1 x USB 10 Gbps USB Type-C [™] female 1 x USB 10 Gbps Type-A female
Internal:	1 x SATA 15 pin plug 1 x PCI Express x4, V3.0

Technical characteristics

Chipset:	Asmedia ASM2142
Data transfer rate:	USB 10 Gbps up to 10 Gb/s