

# Delock USB 3.1 Gen 2 Slot Bracket with 2 x USB Type-C<sup>™</sup> Ports

## Description

With this slot bracket by Delock a PC can be extended by two USB Type-C<sup>TM</sup> ports. At each port max. 20 V / 3 A and a data transfer rate of up to 10 Gbps are available.



#### Item no. 89935

EAN: 4043619899357 Country of origin: China Package: Zip poly bag

# **Specification**

- Connectors: internal: 2 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) key A male external: 2 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C<sup>™</sup> female
- Voltage: max. 20 V
- Current: max. 3 A
- Cable colour: black
- Cable length: ca. 50 cm

## System requirements

- PC with one free slot
- Linux Kernel 3.10 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- Motherboard with two free USB key A female ports

## Package content



Slot bracket

#### Images





#### General

Form factor:	Low Profile
Specification:	RS-232 (EIA / TIA) PCIe 1.1
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Slot:	PCIe

# Interface

External:	1 x DB44 1 x Serial RS-232 DB9 plug 2 x USB 10 Gbps USB Type-C™ female
Internal:	1 x SATA 15 pin plug 1 x PCI Express x1, V1.1 2 x USB 10 Gbps key A male

# **Technical characteristics**

Chipset:	WCH384L
Data transfer rate:	10 Gbps up to 230.4 Kb/s 4 x up to 230,4 Kbps
FIFO:	4 x 256 Byte
Jumper:	8 x
Operating temperature:	-40 °C ~ 85 °C
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Voltage:	5 V or 12 V can be set individually for each port through the jumper (pin 1 or 9)
UART:	16C950

# **DATASHEET**



Data bits:

4, 5, 6, 7, 8





# **Physical characteristics**

Cable type:	UL AWM Style 2464 30 AWG 80 °C 300 V VW-1
Cable colour:	black
Cable length:	50 cm 25 cm
Pin finishing:	gold-plated
Screw type:	#4-40 UNC
Slot bracket:	standard Low Profile
Length:	94.3 mm
Width:	63.3 mm
Height:	14.0 mm
Colour:	green