


Delock PCI Express x1 Card to 1 x Serial RS-232

Description

The PCI Express card by Delock expands a PC by one external serial port. Different devices such as scanner, protocol converter, IoT devices etc. can be connected to this card.

Low Profile Form Factor

By using the included low profile bracket, the PCI Express card can be also installed into a Mini-PC.



Item no. 90006

EAN: 4043619900060

Country of origin: China

Package: Retail Box

Specification

- Connectors:
external: 1 x serial RS-232 DB9 male
internal: 1 x PCI Express x1, V2.0
- Chipset: ASIX AX99100
- Compatible with 16C950 UART
- Supports Active State Power Management (ASPM)
- Supports Direct Memory Access (DMA)
- Data transfer rate up to 921.6 Kbps
- FIFO: 256 byte
- Databits: 5, 6, 7, 8, 9
- Stop bits: 1, 1.5, 2
- Parity: even, odd, none, mark, space
- Flow control: none, hardware RTS / CTS, software XON / XOFF
- Operating temperature: 0 °C ~ 70 °C

System requirements


- Linux Kernel 2.6.24 or above
- Windows 8.1/8.1-64/10/10-64/11

- PC with one free PCI Express slot

Package content

- PCI Express card
- Low profile bracket
- Driver CD
- User manual

Images



General

| | |
|-----------------------------|--|
| Form factor: | Low Profile (MD1) |
| Specification: | PCI Express 2.0 |
| Supported operating system: | Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11 |
| Slot: | PCIe |

Interface

| | |
|-----------|----------------------------|
| External: | 1 x Serial RS-232 DB9 male |
| Internal: | 1 x PCI Express x1, V2.0 |

Technical characteristics

| | |
|---------------------|---|
| Chipset: | ASIX AX99100 |
| Data transfer rate: | 75, 110, 134, 150, 300, 600, 1200, 1800, 2400, 4800, 7200, 9600, 14400, 19200, 38400, 57600, 115200, 230400, 460800, 921600 |
| FIFO: | 1 x 256 Byte |
| UART: | 16C950 |

Physical characteristics

| | |
|---------------|----------------------|
| Slot bracket: | Low Profile standard |
| Colour: | green |