
Delock 2.5” SATA Card Reader for CFast memory cards

Description

The card reader by Delock can be used for reading and writing **CFast memory cards**, which can be used as a 2.5″ HDD / SSD. The optional CFast card works as additional storage space, as well as HDD for an operating system. The card reader can be installed into the system internally through a SATA 22 pin interface.



Item no. 91750

EAN: 4043619917501

Country of origin: Taiwan, Republic of China

Package: Retail Box

Specification

- Connectors:
  1 x SATA 6 Gb/s 22 pin plug
  1 x CFast slot
- Supports CFast type I / II memory cards
- 2 x LED indicator for power and activity
- Bootable
- Supports S.M.A.R.T.
- Supports TRIM
- Supports DevSleep
- Hot Swap
- Dimensions (LxWxH): ca. 100 x 70 x 8 mm
- OS independent, no driver installation necessary

System requirements

- A free SATA 22 pin interface

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.


Package content

- Card reader SATA to CFast
- 4 x screw
- User manual

Images







© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Form factor:	2.5"
Function:	bootable
Supported operating system:	OS independent, no driver installation necessary
Supported memory card:	CFast type I / II

Interface

Connector 1:	1 x SATA 6 Gb/s 22 pin plug
Connector 2:	1 x CFast slot

Physical characteristics

Length:	100 mm
Width:	70 mm
Height:	8 mm

© 2024 by Tragant. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.