


Delock USB 2.0 Camera Module 1.92 Megapixel 55° Fix Focus

Description

The Delock USB 2.0 camera module offers in compact construction low power consumption as well as high resolution. It is ideal for installation in industry components like IPCs, sensors, notebooks or PDAs.



Item no. 95950

EAN: 4043619959501

Country of origin: China

Package:

Specification

- USB 2.0 High Speed
- 1.92 megapixel
- With optical IR filter
- Status indication with LED
- UXGA 1600x1200, 15 fps
- HD ready 1280 x 720 p, 30 fps
- SVGA 800 x 600, 30 fps
- QVGA 320 x 280, 60 fps
- Lens: F/2.8
- Viewing angle horizontal: depends on the resolution 31° ~ 64°
- Fix focus: 20 cm ~ infinite
- Automatic exposure control + white balance (disengageable)
- Format: YUY2, RGB24, I420
- Standard USB video class device UVC
- Win XP(SP2)/Vista7/8, Linux 2.6.15
- Mac OS 10.4.8; ab P4 1,4 128MB
- Voltage: 5 V DC USB
- Elektrical power: 600 mW
- Dimension LxBxH: 60.80 x 8.10 x 6.30 mm

System requirements

- Win XP(SP2) / Vista/ 7/ 8,
- MS DirectX 9.0c and above
- Linux 2.6.15 and above with Linux UVC open source driver

<http://linux-uvc.berlios.de>

- Mac OS 10.4.8 and above
 - Minimum P4 1.4 GHz, 128 MB RAM
-

Package content

- Camera module
-

Images

